



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

REC'D 24 MAY 2004

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03251849.0

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:
Application no.: 03251849.0
Demande no:

Anmeldetag:
Date of filing: 25.03.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

SHELL INTERNATIONALE RESEARCH
MAATSCHAPPIJ B.V.
Carel van Bylandtlaan 30
2596 HR Den Haag
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Water intake riser

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

B63B35/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT SE SI SK TR LI

WATER INTAKE RISER

The present invention relates to a water intake riser. Such a water intake riser is used on a vessel to provide cooling water to a heat exchanger. In particular such a water intake riser is used on a vessel on which a plant for liquefying natural gas is arranged. In the specification and in the claims the word vessel is used to refer to a ship, a barge, a floating platform and so on.

An example of such a riser is described in the article by R Franciss, Maximum stress model test of a seawater lift casing to a Petrobras PXXV platform in Albacora field, presented at 9th International symposium on Offshore Engineering, September 1995. The paper describes a floating offshore platform provided with water intake risers that are hingeably connected to the submerged pontoons of the platform.

It is an object of the present invention to provide a water intake riser having a simple and reliable design.

To this end the water intake riser that can be suspended from a vessel according to the present invention comprises a riser connected to a riser hanger, which riser hanger comprises a first tubular element, a second tubular element to which the riser is connected, a flexible load transfer element joining the tubular elements, and a hose of which the ends are secured to the adjacent ends of the tubular elements.

The invention further relates to a vessel provided with a water intake riser.

The invention will now be described by way of example with reference to the accompanying drawings, wherein

Figure 1 shows schematically and not to scale a partial longitudinal section of the water intake riser according to the present invention;

Figure 2 shows a section along line II-II of Figure 1;

Figure 3 shows schematically and not to scale a cross-section of the bottom of a vessel provided with three water intake risers according to the present invention; and

Figure 4 shows schematically and on a larger scale detail IV of Figure 3.

Reference is now made to Figure 1 showing schematically and not to scale the water intake riser 1 according to the present invention. The water intake riser 1 suspended from a hull 2 of a vessel (not shown). The water intake riser 1 comprises an elongated tube 3 connected to a riser hanger 4. The riser hanger 4 comprises two tubular elements, a first tubular element 6 and a second tubular element 7. The upper end part of the first tubular element 6 has an open end provided with a hanger cup 8. The hanger cup 8 matches with a suitably formed opening 10 in the hull 2 so that the first tubular element 6 is supported in the opening 10. Securing the first tubular element 6 to the vessel (not shown) allows suspending the water intake riser 1 from the hull 2.

The riser hanger 4 further comprises a second tubular element 7. The upper end of the elongated tube 3 is connected to the lower end of the second tubular element 7 by any suitable means.

The riser hanger 4 further comprises a flexible load transfer element 16 joining the tubular elements 6 and 7. In the embodiment shown in Figure 1, the flexible load transfer element 16 is a chain. The riser hanger 4 further comprises a hose 17 of which the ends are secured to the adjacent end parts 19 and 20 of the tubular

elements 6 and 7. The hose 17 is secured in a watertight way to the end parts 19 and 20.

Suitably, each tubular element 6 and 7 is provided with a cross-shaped internal 22 (see also Figure 2) having means 23 for securing the flexible load transfer element to the internal 22. The cross-shaped internal 22 is suitably welded to the inner surface of the tubular element 6 or 7. For the sake of simplicity the welds have not been shown.

In the water intake riser 1 of the present invention the hose 17 forms a conduit for water, whereas the flexible load transfer element 16 transfers the self-weight and the dynamic loads of the elongated tube 3 to the first tubular element 6. In this way the function of transferring water is separated from transferring a load.

Reference is now made to Figure 3. Figure 3 shows the lower part of a vessel 30 provided with at least two water intake risers. In this case the vessel 30 is provided with three water intake risers according to the present invention, wherein the first tubular element is secured to the vessel 30 and suspended from the hull 2 as shown in more detail in Figure 1.

In order to prevent the water intake risers 1 to collide, there is provided at least one riser-spacer 35. In Figure 3 only one riser-spacer 35 is shown.

The riser-spacer 35 comprises interconnected guide sleeves 36, one guide sleeve 36 for each water intake riser 1. Bars 37 form the interconnection. Each guide sleeve 36 defines an aperture 40 (see Figure 4), which aperture 40 allows the elongated tubes 3 to pass freely through it and allows limited rotation of the elongated tubes 3 about a horizontal axis 43. The horizontal axis 43 is an axis that is lying in a plane of symmetry of the riser-spacer 35, which plane is perpendicular to the direction of passage through the aperture 40.

The riser-spacer 35 is suspended from the vessel 30 to a predetermined depth. In the embodiment shown in Figure 3, the riser-spacer 35 is suspended by means of a cable 45 secured in the hull 2. In an alternative
5 embodiment a chain replaces the cable, or one of the guide sleeves is secured to a water intake riser.

Suitably the length of the guide sleeve 36 is in the range of one to four times the outer diameter of the riser. The bars 37 interconnecting the guide sleeves 36
10 of the riser-spacer can be replaced by a frame or by a solid polygon. Suitably the thickness of the solid polygon is between three to four times the diameter of a riser in order to prevent vortex shedding of the riser.

The open upper ends of the water intake risers 1 open
15 into a receptacle 46 inside the vessel 30 from which the water is withdrawn (not shown) for use as cooling water.

Suitably the number of water intake risers is between two and eight.

C L A I M S

1. A water intake riser that can be suspended from a vessel comprising a riser connected to a riser hanger, which riser hanger comprises a first tubular element, a second tubular element to which the riser is connected, a flexible load transfer element joining the tubular elements, and a hose of which the ends are secured to the adjacent ends of the tubular elements.

2. The water intake riser according to claim 1, wherein each tubular element is provided with a cross-shaped internal having means for securing the flexible load transfer element to the internal.

3. The water intake riser according to claim 1 or 2, wherein the flexible load transfer element is a chain.

4. Vessel provided with at least one water intake riser according to any one of the claims 1-3, wherein the first tubular element is secured to the vessel.

5. Vessel according to claim 4, which is provided with at least two water intake risers, and with at least one riser-spacer comprising interconnected guide sleeves, one guide sleeve for each riser, wherein each guide sleeve defines an aperture, which aperture allows a riser to pass freely through it and allows limited rotation of the riser about a horizontal axis, and wherein each riser-spacer element is suspended from the vessel to a predetermined depth.

6. Vessel according to claim 5, wherein the number of water intake risers is between two and eight.

7. Vessel according to claim 5 or 6, wherein the length of the guide sleeve is in the range of one to four times the diameter of the riser.

8. Vessel according to any one of the claims 4-7,
wherein the hull of the vessel is provided with at least
one opening, one opening for each water intake riser, and
wherein upper end of the first tubular element of each
water intake riser is supported in the opening.
- 5.

A B S T R A C T

WATER INTAKE RISER

A water intake riser (1) that can be suspended from a vessel comprising a riser (3) connected to a riser hanger (4), which riser hanger (4) comprises a first tubular element (6), a second tubular element (7) to which the riser (3) is connected, a flexible load transfer element (16) joining the tubular elements (6, 7), and a hose (17) of which the ends are secured to the adjacent ends (20, 22) of the tubular elements (6, 7).

(Figure 1)

TS 6393

TS 6393 EPC




FIG. 1

TS6393

TS 6393 EPL






FIG 2

TS6393

TS 6393 E12



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.